





PHOTOLUMINESCENT GRIT TAPE

MODEL P3.375E-T-ECO

(TWO STAGE RIBBED ECO-TREAD BARS)

SPECIFICATIONS:

- ① **BASE:** EXTRUDED ALUMINUM ALLOY 6063 T-6
- ② **ECOTREAD:** RECYCLED RUBBER SHEET 8MM, RECYCLED RUBBER GRANULES ENCAPSULATED IN A WEAR AND WATER RESISTANT ELASTOMETRIC NETWORK
3. **BASE FINISH:** MILL
4. **POURED CONCRETE STAIRS:** NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS
5. **CONCRETE FILLED STEEL PAN STAIRS:** NOSING SHALL BE FULL LENGTH OF STEPS, LESS 1/8" CLEARANCE
6. **COLOR:** BLACK (STANDARD), SAFETY YELLOW, BLACK-BLUE, BLACK-GRAY

7. **LENGTH:** 12'0" MAXIMUM
8. **UL 1994 LISTED:** COMBINED WIDTH OF PHOTO-LUMINESCENT MATERIAL SHALL NOT BE LESS THAN 1"

LENGTH	QTY	COLOR

PROJECT:			
ARCHITECT:			
CONTRACTOR:			
QTY:			
PART#:		STTM-P3.375E-T-ECO	
 9300 73rd Avenue North Minneapolis, MN 55428		TITLE:	
		Two Stage Rib, Stair Tread, Bar Ribbed Eco-Tread Short Nose, Alum Extruded Anchor, Photoluminescent Grit Tape	
NAME	DATE	SIZE	DWG. NO.
DRAWN	DKL	4/3/23	A
RELEASED	GLN	4/3/23	WEIGHT:
			REV A
			SHEET 1 OF 1